INDOOR - SUSPENSION

ASTRELLE GLOBAL

- alluminio, vetro soffiato a bocca
- colore cavo: nero

- aluminum, mouthblown glass
- cable color: black



Con rosone e driver
With canopy and driver



3021	M 2700K		W 3000K	
Power	↑6.0W	↓9.7W	↑6.0W	↓9.7W
Nominal lumen	↑714.0lm	↓1401.0lm	↑724.0lm	↓1475.0lm
Beam angle	↑diffused	↓150°	↑diffused	↓150°
CRI	>90		>90	
Supply	220-240V		220-240V	

Item	Temperature	Canopy	Body	Glass
3021	**M**	**-FS**	**-FS**	**-ANE**
composed by RS04/03 (1Pz) 3025 (1Pz)	**W**			

Con rosone scorrevole e driver
With sliding canopy and driver



3029	M 2700K		W 3000K	
Power	↑24.0W	↓38.8W	↑24.0W	↓38.8W
Nominal lumen	↑2856.0lm	↓5604.0lm	↑2896.0lm	↓5900.0lm
Beam angle	↑diffused	↓150°	↑diffused	↓150°
CRI	>90		>90	
Supply	220-240V		220-240V	

Item	Temperature	Canopy	Body	Glass
3029	**M**	**-BI**	**-FS**	**-ANE**
composed by RS94/01 (1Pz) 3025 (4Pz)	**W**	**-NE**		

Con rosone per incasso, senza driver
With recessed canopy, without driver

Necessita di driver remoto a 500mA oppure di convertitore da 48Vdc a 500mA più driver a 48Vdc
Requires 500mA remote driver, or 48Vdc to 500 mA converter and 48Vdc driver



3023	M 2700K		W 3000K	
Power	↑6.0W	↓9.7W	↑6.0W	↓9.7W
Nominal lumen	↑714.0lm	↓1401.0lm	↑724.0lm	↓1475.0lm
Beam angle	↑diffused	↓150°	↑diffused	↓150°
CRI	>90		>90	
Supply	500mA		500mA	

Item	Temperature	Canopy	Body	Glass
3023	M	-NE	-FS	-ANE
composed by RS97 (1Pz) 3025 (1Pz)	W			

Solo corpo
Body only

Necessita di driver remoto a 500mA oppure di convertitore da 48Vdc a 500mA più driver a 48Vdc
Requires 500mA remote driver, or 48Vdc to 500 mA converter and 48Vdc driver



3025	M 2700K		W 3000K	
Power	↑6.0W	↓9.7W	↑6.0W	↓9.7W
Nominal lumen	↑714.0lm	↓1401.0lm	↑724.0lm	↓1475.0lm
Beam angle	↑diffused	↓150°	↑diffused	↓150°
CRI	>90		>90	
Supply	500mA		500mA	

Item	Temperature	Body	Glass
3025	M	-FS	-ANE
	W		

Solo corpo con cavo 5m
Body only with 5m cable

Necessita di driver remoto a 500mA oppure di convertitore da 48Vdc a 500mA più driver a 48Vdc
Requires 500mA remote driver, or 48Vdc to 500 mA converter and 48Vdc driver



3027	M 2700K		W 3000K	
Power	↑6.0W	↓9.7W	↑6.0W	↓9.7W
Nominal lumen	↑714.0lm	↓1401.0lm	↑724.0lm	↓1475.0lm
Beam angle	↑diffused	↓150°	↑diffused	↓150°
CRI	>90		>90	
Supply	500mA		500mA	

Item	Temperature	Body	Glass
3027	M	-FS	-ANE
	W		

Driver in corrente in remoto 500mA
500mA remote constant current driver

Item	items powerable	Power	IP	Dimensions	Dimming
1A1858/01	1	20W	IP20	75x40x21	PUSH | DALI

Convertitore da 48Vdc a 500mA
48Vdc to 500 mA converter

Necessita di driver remoto a 48Vdc
Requires 48V remote driver



Item	items powerable
2A7900	1

Driver 48Vdc in tensione in remoto
Remote constant voltage drivers 48Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
1A0633	1-3	70W	IP20	210x45x49	ON-OFF
1A0634	1-6	150W	IP20	210x45x49	ON-OFF
1A1239	1-12	240W	IP67	244x68x39	ON-OFF
1A2493	1-18	320W	IP67	252x90x44	ON-OFF

Centraline dimmerabili in remoto
Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
1A0837/48	288W	IP20	132x22x20	PUSH | DALI | 1-10V
1A0838/48	576W	IP20	164x38x25	PUSH | DALI | 0.1-10V