


INDOOR - CEILING

# BEAM MASTER Ø25




- alluminio

- aluminum



**Con rosone, senza driver**  
With canopy, without driver




Item	Temperature	°Optic	Ring	Body
<b>4360</b>	<b>M</b>	<b>06</b>	<b>-BO</b>	<b>-BO</b>
<b>Power</b>	<b>W</b>	<b>35</b>	<b>-NO</b>	<b>-NO</b>
<b>Nominal lumen</b>	<b>N</b>		<b>-BV</b>	<b>-BV</b>
<b>CRI</b>			<b>-OR</b>	<b>-OR</b>
<b>Supply</b>			<b>-RR</b>	<b>-RR</b>
			<b>-TI</b>	<b>-TI</b>

**Con rosone per incasso, senza driver**  
With recessed canopy, without driver




Necessita di controcassa CN25  
Requires CN25 outercasing




Item	Temperature	°Optic	Canopy	Ring	Body
<b>4390</b>	<b>M</b>	<b>06</b>	<b>-NE</b>	<b>-BO</b>	<b>-BO</b>
<b>Power</b>	<b>W</b>	<b>35</b>		<b>-NO</b>	<b>-NO</b>
<b>Nominal lumen</b>	<b>N</b>			<b>-BV</b>	<b>-BV</b>
<b>CRI</b>				<b>-OR</b>	<b>-OR</b>
<b>Supply</b>				<b>-RR</b>	<b>-RR</b>
				<b>-TI</b>	<b>-TI</b>

## Controcassa

### Outercasing



Ø66,5



39,6

Item	Finish
<b>CN25</b>	<b>-NA</b> <span style="display: inline-block; width: 15px; height: 15px; background-color: black; vertical-align: middle;"></span>

## Driver 24Vdc in tensione in remoto

Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
<b>1A0150</b>	1-4	30W	IP20	154x50x14	ON-OFF
<b>1A1910</b>	1-8	60W	IP20	185x63,5x22	ON-OFF
<b>1A1476</b>	1-7	100W	IP20	177x56,4x17,2	ON-OFF
<b>1A2168</b>	1-15	100W	IP20	190x65x22	PUSH   DALI
<b>1A1999</b>	1-15	100W	IP20	201x63x30	L-C

## Centraline dimmerabili in remoto

Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
<b>1A0837/24</b>	144W	IP20	132x22x20	PUSH   DALI   1-10V
<b>1A0838/24</b>	288W	IP20	164x38x25	PUSH   DALI   0.1-10V