INDOOR - CEILING

BEAM MASTER Ø35

- alluminio

- aluminum



Con rosone, senza driver

With canopy, without driver



4361	**M** 2700K	**W** 3000K	**N** 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	24Vdc	24Vdc	24Vdc

Item	**Temperature**	**°Optic**	**Ring**	**Body**
4361	**M**	**15**	**-BO**	**-BO**
	W	**36**	**-NO**	**-NO**
	N		**-BV**	**-BV**
			-OR	**-OR**
			-RR	**-RR**
			-TI	**-TI**

Con rosone per incasso, senza driver

With recessed canopy, without driver

Necessita di controcassa CN25

Requires CN25 outercasing



4391	**M** 2700K	**W** 3000K	**N** 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	24Vdc	24Vdc	24Vdc

Item	**Temperature**	**°Optic**	**Canopy**	**Ring**	**Body**
4391	**M**	**15**	**-NE**	**-BO**	**-BO**
	W	**36**		**-NO**	**-NO**
	N			**-BV**	**-BV**
				-OR	**-OR**
				-RR	**-RR**
				-TI	**-TI**

Controcassa
Outercasing



Item	Finish
CN25	**-NA**

Driver 24Vdc in tensione in remoto
Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
1A0150	1-2	30W	IP20	154x50x14	ON-OFF
1A1910	1-4	60W	IP20	185x63,5x22	ON-OFF
1A1476	1-7	100W	IP20	177x56,4x17,2	ON-OFF
1A2168	1-7	100W	IP20	190x65x22	PUSH | DALI
1A1999	1-7	100W	IP20	201x63x30	L-C

Centraline dimmerabili in remoto
Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
1A0837/24	144W	IP20	132x22x20	PUSH | DALI | 1-10V
1A0838/24	288W	IP20	164x38x25	PUSH | DALI | 0.1-10V