


INDOOR - CEILING

# BEAM MASTER Ø35




- alluminio

- aluminum



## Con rosone, senza driver

With canopy, without driver




	M 2700K	W 3000K	N 4000K
<b>Power</b>	6.6W	6.6W	6.6W
<b>Nominal lumen</b>	700.0lm	733.0lm	785.0lm
<b>CRI</b>	>90	>90	>90
<b>Supply</b>	24Vdc	24Vdc	24Vdc

Item	Temperature	°Optic	Ring	Body
<b>4361</b>	<b>M</b>	<b>15</b>	<b>-BO</b>	<b>-BO</b>
	<b>W</b>	<b>36</b>	<b>-NO</b>	<b>-NO</b>
	<b>N</b>		<b>-BV</b>	<b>-BV</b>
			<b>-OR</b>	<b>-OR</b>
			<b>-RR</b>	<b>-RR</b>
			<b>-TI</b>	<b>-TI</b>

## Con rosone per incasso, senza driver

With recessed canopy, without driver

Necessita di controcassa CN25  
Requires CN25 outercasing





	M 2700K	W 3000K	N 4000K
<b>Power</b>	6.6W	6.6W	6.6W
<b>Nominal lumen</b>	700.0lm	733.0lm	785.0lm
<b>CRI</b>	>90	>90	>90
<b>Supply</b>	24Vdc	24Vdc	24Vdc

Item	Temperature	°Optic	Canopy	Ring	Body
<b>4391</b>	<b>M</b>	<b>15</b>	<b>-NE</b>	<b>-BO</b>	<b>-BO</b>
	<b>W</b>	<b>36</b>		<b>-NO</b>	<b>-NO</b>
	<b>N</b>			<b>-BV</b>	<b>-BV</b>
				<b>-OR</b>	<b>-OR</b>
				<b>-RR</b>	<b>-RR</b>
				<b>-TI</b>	<b>-TI</b>

## Controcassa

### Outercasing



Item	Finish
<b>CN25</b>	<b>-NA</b> 

### Driver 24Vdc in tensione in remoto

Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
<b>1A0150</b>	1-2	30W	IP20	154x50x14	ON-OFF
<b>1A1910</b>	1-4	60W	IP20	185x63,5x22	ON-OFF
<b>1A1476</b>	1-7	100W	IP20	177x56,4x17,2	ON-OFF
<b>1A2168</b>	1-7	100W	IP20	190x65x22	PUSH   DALI
<b>1A1999</b>	1-7	100W	IP20	201x63x30	L-C

### Centraline dimmerabili in remoto

Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
<b>1A0837/24</b>	144W	IP20	132x22x20	PUSH   DALI   1-10V
<b>1A0838/24</b>	288W	IP20	164x38x25	PUSH   DALI   0.1-10V