INDOOR - CEILING

BEAM MASTER Ø60

- alluminio

- aluminum



Con rosone, senza driver

With canopy, without driver



4362	M 2700K	W 3000K	N 4000K
Power	9.4W	9.4W	9.4W
Nominal lumen	1090.4lm	1137.4lm	1175.0lm
CRI	>90	>90	>90
Supply	24Vdc	24Vdc	24Vdc

Item	Temperature	°Optic	Ring	Body
4362	M	12	-BO	-BO
	W	35	-NO	-NO
	N	55	-BV	-BV
			-OR	-OR
			-RR	-RR
			-TI	-TI

Con rosone per incasso, senza driver

With recessed canopy, without driver

Necessita di controcassa CN25

Requires CN25 outercasing



4392	M 2700K	W 3000K	N 4000K
Power	9.4W	9.4W	9.4W
Nominal lumen	1090.4lm	1137.4lm	1175.0lm
CRI	>90	>90	>90
Supply	24Vdc	24Vdc	24Vdc

Item	Temperature	°Optic	Canopy	Ring	Body
4392	M	12	-NE	-BO	-BO
	W	35		-NO	-NO
	N	55		-BV	-BV
				-OR	-OR
				-RR	-RR
				-TI	-TI

Controcassa
Outercasing



Item	Finish
CN25	**-NA**

Driver 24Vdc in tensione in remoto
Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
1A0150	1-2	30W	IP20	154x50x14	ON-OFF
1A1910	1-4	60W	IP20	185x63,5x22	ON-OFF
1A1476	1-7	100W	IP20	177x56,4x17,2	ON-OFF
1A2168	1-7	100W	IP20	190x65x22	PUSH | DALI
1A1999	1-7	100W	IP20	201x63x30	L-C

Centraline dimmerabili in remoto
Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
1A0837/24	144W	IP20	132x22x20	PUSH | DALI | 1-10V
1A0838/24	288W	IP20	164x38x25	PUSH | DALI | 0.1-10V