INDOOR - SUSPENSION

BEAM STICK METAL Ø35 H200

- alluminio
- colore cavo: nero

- aluminum
- cable color: black



Con rosone e driver
With canopy and driver

4565	**M** 2700K	**W** 3000K	**N** 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	220-240V	220-240V	220-240V

Item	Temperature	°Optic	Canopy	Ring	Body
4565 composed by RS03/02 (1Pz) 4532 (1Pz)	**M** **W** **N**	**15** **36**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**

Con rosone e driver
With canopy and driver

4627	**M** 2700K	**W** 3000K	**N** 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	220-240V	220-240V	220-240V

Item	Temperature	°Optic	Canopy	Ring	Body
4627 composed by RS03/03 (1Pz) 4532 (1Pz)	**M** **W** **N**	**15** **36**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**

Con rosone e driver
With canopy and driver

4628	M 2700K	W 3000K	N 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	220-240V	220-240V	220-240V

Item	Temperature	°Optic	Canopy	Ring	Body
4628 composed by RS03/04 (1Pz) 4532 (1Pz)	**M** **W** **N**	**15** **36**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**

Con rosone, senza driver
With canopy, without driver

Necessita di driver remoto a 500mA oppure di convertitore da 24Vdc a 500mA più driver a 24Vdc
Requires 500mA remote driver, or 24Vdc to 500 mA converter and 24Vdc driver



4563	M 2700K	W 3000K	N 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	500mA	500mA	500mA

Item	Temperature	°Optic	Canopy	Ring	Body
4563 composed by RS01 (1Pz) 4532 (1Pz)	**M** **W** **N**	**15** **36**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**

Con rosone piatto per cartongesso, senza driver
With flat rosette for plasterboard, without driver

Necessita di driver remoto a 500mA oppure di convertitore da 24Vdc a 500mA più driver a 24Vdc
Requires 500mA remote driver, or 24Vdc to 500 mA converter and 24Vdc driver



4564	M 2700K	W 3000K	N 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	500mA	500mA	500mA

Item	Temperature	°Optic	Canopy	Ring	Body
4564 composed by RS06 (1Pz) 4532 (1Pz)	**M** **W** **N**	**15** **36**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**	**-BO** **-NO** **-BV** **-OR** **-RR** **-TI**

Solo corpo
Body only

Necessita di driver remoto a 500mA oppure di convertitore da 24Vdc a 500mA più driver a 24Vdc
Requires 500mA remote driver, or 24Vdc to 500 mA converter and 24Vdc driver



4532	M 2700K	W 3000K	N 4000K
Power	6.6W	6.6W	6.6W
Nominal lumen	700.0lm	733.0lm	785.0lm
CRI	>90	>90	>90
Supply	500mA	500mA	500mA

Item	Temperature	°Optic	Ring	Body
4532	M	15	-BO	-BO
	W	36	-NO	-NO
	N		-BV	-BV
			-OR	-OR
			-RR	-RR
			-TI	-TI

Driver in corrente in remoto 500mA
500mA remote constant current driver

Item	items powerable	Power	IP	Dimensions	Dimming
1A2399	1	10W	IP20	102x38x21	L-C

Convertitore da 24Vdc a 500mA
24Vdc to 500 mA converter

Necessita di driver remoto a 24Vdc
Requires 24V remote driver



Item	items powerable
2A4843	1

Driver 24Vdc in tensione in remoto
Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
1A0150	1-2	30W	IP20	154x50x14	ON-OFF
1A1910	1-4	60W	IP20	185x63,5x22	ON-OFF
1A1476	1-7	100W	IP20	177x56,4x17,2	ON-OFF
1A2168	1-7	100W	IP20	190x65x22	PUSH | DALI
1A1999	1-7	100W	IP20	201x63x30	L-C

Centraline dimmerabili in remoto
Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
1A0837/24	144W	IP20	132x22x20	PUSH | DALI | 1-10V
1A0838/24	288W	IP20	164x38x25	PUSH | DALI | 0.1-10V

Jack per track 48V + Connettore nero
Jack for track 48V + black connector







Item	Finish	Dimming
201/01	**-JBI** **-JNE**	ON-OFF
201/02	**-JBI** **-JNE**	0-10V
201/03	**-JBI** **-JNE**	DALI

Jack per track 230V + Connettore nero
Jack for track 230V + black connector









Item	Finish	Dimming
211/02	**-JBI** **-JNE**	ON-OFF
211/05	**-JBI** **-JNE**	L-C
211/06	**-JBI** **-JNE**	DALI
211/09	**-JBI** **-JNE**	CASAMBI

Passacavi
Cable entry



Item	Finish	
BEAMKIT01	**-NA**	■
BEAMKIT02	**-NA**	■