



INDOOR - CEILING

## EYE SPOT



- alluminio

- aluminum



	<b>M 2700K</b>	<b>W 3000K</b>	<b>N 4000K</b>
<b>Power</b>	6.6W	6.6W	6.6W
<b>Nominal lumen</b>	700.0lm	733.0lm	785.0lm
<b>CRI</b>	>90	>90	>90
<b>Supply</b>	24Vdc	24Vdc	24Vdc
Item	Temperature	°Optic	Finish
<b>3780</b>	<b>M</b>	<b>14</b>	<b>-BO</b>
	<b>W</b>	<b>36</b>	<b>-NO</b>
	<b>N</b>		<b>-BV</b>
			<b>-OR</b>
			<b>-TI</b>

**Driver 24Vdc in tensione in remoto**

Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
<b>1A0150</b>	1-2	30W	IP20	154x50x14	ON-OFF
<b>1A1910</b>	1-4	60W	IP20	185x63,5x22	ON-OFF
<b>1A1476</b>	1-7	100W	IP20	177x56,4x17,2	ON-OFF
<b>1A2168</b>	1-7	100W	IP20	190x65x22	PUSH   DALI
<b>1A1999</b>	1-7	100W	IP20	201x63x30	L-C

**Centraline dimmerabili in remoto**

Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
<b>1A0837/24</b>	144W	IP20	132x22x20	PUSH   DALI   1-10V
<b>1A0838/24</b>	288W	IP20	164x38x25	PUSH   DALI   0.1-10V