


INDOOR - SUSPENSION

LIKESHADE



- alluminio, ottone, ferro

- aluminum, brass, iron



Con rosone e driver
With canopy and driver




	M 2700K		W 3000K	
Power	↑ 9.4W	↓ 9.4W	↑ 9.4W	↓ 9.4W
Nominal lumen	↑ 1090.4lm	↓ 1090.4lm	↑ 1137.4lm	↓ 1137.4lm
Beam angle	↑ 120°	↓ 50°	↑ 120°	↓ 50°
CRI	>90		>90	
Supply	220-240V		220-240V	

Item	Temperature	°Optic	Canopy	Body
2304	M	50	-BV	
			-NE	
	-OR			
	-TI			
W	-BV			
	-NO			

...composed by
RS66/01 (1Pz)
2306 (1Pz)

Con rosone per incasso, senza driver
With recessed canopy, without driver

Necessita di driver remoto a 500mA
Requires 500mA remote driver



	M 2700K		W 3000K	
Power	↑ 9.4W	↓ 9.4W	↑ 9.4W	↓ 9.4W
Nominal lumen	↑ 1090.4lm	↓ 1090.4lm	↑ 1137.4lm	↓ 1137.4lm
Beam angle	↑ 120°	↓ 50°	↑ 120°	↓ 50°
CRI	>90		>90	
Supply	500mA		500mA	

Item	Temperature	°Optic	Canopy	Body
2307	M	50	-NE	
			-BV	
	-OR			
	-TI			
W	-BV			
	-NO			

...composed by
RS96 (1Pz)
2306 (1Pz)

Driver in corrente in remoto 500mA
500mA remote constant current driver

Item	items powerable	Power	IP	Dimensions	Dimming
1A1858/01	1	20W	IP20	75x40x21	PUSH DALI