INDOOR - SUSPENSION

LIKESHADOW

- alluminio, ottone, ferro, fibra di carbonio

- aluminum, brass, iron, carbon fiber



Con rosone e driver
With canopy and driver



2305	M 2700K		W 3000K	
Power	↑9.4W	↓9.4W	↑9.4W	↓9.4W
Nominal lumen	↑1090.4lm	↓1090.4lm	↑1137.4lm	↓1137.4lm
Beam angle	↑120°	↓50°	↑120°	↓50°
CRI	>90		>90	
Supply	220-240V		220-240V	

Item	Temperature	°Optic	Canopy	Body
2305	**M**	**50**	**-BV**	**-BV**
composed by	**W**		**-NE**	**-NO**
RS66/01 (1Pz)			**-OR**	**-OR**
2302 (1Pz)			**-TI**	**-TI**
2306 (1Pz)				

Con rosone per incasso, senza driver
With recessed canopy, without driver

Necessita di driver remoto a 500mA
Requires 500mA remote driver



2308	M 2700K		W 3000K	
Power	↑9.4W	↓9.4W	↑9.4W	↓9.4W
Nominal lumen	↑1090.4lm	↓1090.4lm	↑1137.4lm	↓1137.4lm
Beam angle	↑120°	↓50°	↑120°	↓50°
CRI	>90		>90	
Supply	500mA		500mA	

Item	Temperature	°Optic	Canopy	Body
2308	**M**	**50**	**-NE**	**-BV**
composed by	**W**			**-NO**
RS96 (1Pz)				**-OR**
2302 (1Pz)				**-TI**
2306 (1Pz)				

Driver in corrente in remoto 500mA
500mA remote constant current driver

Item	items powerable	Power	IP	Dimensions	Dimming
1A1858/01	1	20W	IP20	75x40x21	PUSH | DALI