


OUTDOOR - FLOOR

# MAXI DOT SPOT




- alluminio, vetro



- aluminum, glass



117	M 2700K	W 3000K	N 4000K
<b>Power</b>	9.4W	9.4W	9.4W
<b>Nominal lumen</b>	1090.4lm	1137.4lm	1175.0lm
<b>CRI</b>	>90	>90	>90
<b>Supply</b>	24Vdc	24Vdc	24Vdc




Item	Temperature	°Optic	Finish
117	<b>M</b>	<b>00</b>	-AA
	<b>W</b>	<b>12</b>	-BA
	<b>N</b>	<b>35</b>	-NA
		<b>55</b>	

## Versione RGBW

RGBW version



117	RGBW RGB + 3000K
<b>Power</b>	7.9W
<b>Nominal lumen</b>	446.0lm
<b>CRI</b>	90
<b>Supply</b>	700mA



Item	Temperature	°Optic	Finish
117	<b>RGBW</b>	<b>26</b>	-AA
		<b>36</b>	-BA
		<b>60</b>	-NA

## Accessori

Accessories


Picchetto  
Peg




Item
<b>PC</b>

Ghiera e visiera anti-abbagliamento  
Ring and antiglare visor

512

-NA 

Cinghia di fissaggio  
Fixing belt



515

### Controller per versione RGBW

Controller for RGBW version

Controller 4 canali - CC  
4-channels controller - CC

Item	Power	IP	Dimensions	Dimming
<b>1A0521/01</b>	17W	IP20	90x71x58	PUSH

Controller 4 canali - CC  
4-channels controller - CC

<b>1A0521/03</b>	17W	IP20	90x71x58	DALI
------------------	-----	------	----------	------

Controller 4 canali - CC  
4-channels controller - CC

<b>1A0521/04</b>	17W	IP20	90x71x58	DMX
------------------	-----	------	----------	-----

### Driver 24Vdc in tensione in remoto

Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
<b>1A0143</b>	1	14W	IP67	85x39x19	ON-OFF
<b>1A3004</b>	1-2	40W	IP67	148x40x30	ON-OFF
<b>1A3005</b>	1-6	100W	IP67	190x52x33	ON-OFF
<b>1A2386</b>	1-8	120W	IP67	191x63x37,5	DALI
<b>1A2387</b>	1-10	200W	IP67	195x68x39,5	DALI   PUSH