


INDOOR - TRACK 48V

ORNATO TRACK 48V




- alluminio, ferro
- binario escluso

- aluminum, iron
- track excluded



Modulo quadrato "Q"

Squared-shaped module "Q"



2568 M 2700K

Power 20.0W

Nominal lumen 2750.0lm


CRI 80

Supply 48Vdc

Item	Temperature	Adapter	Plate	Decoration
2568	M	-JNE	-OP	-BP

Modulo fiore "F"

Flower-shaped module "F"



2569 M 2700K

Power 20.0W

Nominal lumen 2750.0lm

CRI 80

Supply 48Vdc

Item	Temperature	Adapter	Plate	Decoration
2569	M	-JNE	-OP	-BP

Driver 48Vdc in tensione in remoto


Remote constant voltage drivers 48Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
1A0633	1-2	70W	IP20	210x45x49	ON-OFF
1A0634	1-5	150W	IP20	210x45x49	ON-OFF
1A1239	1-8	240W	IP67	244x68x39	ON-OFF
1A2493	1-10	320W	IP67	252x90x44	ON-OFF

Driver 48Vdc in tensione integrabili nel binario a plafone


Constant voltage drivers 48Vdc fully integrable into ceiling-mounted track

	Item	items powerable	Power	IP	Dimensions	Dimming
Colore Nero, Bianco su richiesta Black finish, White available on request	1A1681	1-4	100W	IP20	298x16x19	DALI

**Driver 48Vdc in tensione semi-integrabili nel binario a plafone**

Constant voltage drivers 48Vdc semi-recessed into ceiling-mounted track

	Item	items powerable	Power	IP	Dimensions	Dimming
Colore Nero, Bianco su richiesta Black finish, White available on request	1A2987	1-8	250W	IP20	268x43,5x22	DALI

**Centraline dimmerabili semi-integrabili nel binario**

Dimmable controllers semi-recessed into track

Permette di collegare 64 lampade DALI ripartite su 8 gruppi

Allows to connect up to 64 DALI lamps, splitted up to 8 groups

	Item	items powerable	Power	IP	Dimensions	Dimming
Colore Nero, Bianco su richiesta Black finish, White available on request	1A1426	1-64	8W	IP20	143x18x58	CASAMBI

