


INDOOR - TRACK 48V

OVERFLY TRACK 48V




- alluminio, metacrilato,
plastica
- binario escluso

- aluminum, methacrylate,
plastic
- track excluded




Per binario PLAFONE
for CEILING track



3406	M 2700K	W 3000K	N 4000K
Power	13.6W	13.6W	13.6W
Nominal lumen	2544.0lm	2584.0lm	2648.0lm
CRI	>90	>90	>90
Supply	48Vdc	48Vdc	48Vdc

Item	Temperature	Adapter	Disk	Stem
3406	M	-JBI		-BO
	W	-JNE		-BV
	N		-NO	-NO
			-OR	-OR
			-RR	-RR
			-TI	-TI


Per binario PLAFONE
for CEILING track



3407	M 2700K	W 3000K	N 4000K
Power	13.6W	13.6W	13.6W
Nominal lumen	2544.0lm	2584.0lm	2648.0lm
CRI	>90	>90	>90
Supply	48Vdc	48Vdc	48Vdc

Item	Temperature	Adapter	Disk	Stem
3407	M	-JBI		-BO
	W	-JNE		-BV
	N		-NO	-NO
			-OR	-OR
			-RR	-RR
			-TI	-TI


Per binario INCASSO for RECESSED track



	M 2700K	W 3000K	N 4000K
Power	13.6W	13.6W	13.6W
Nominal lumen	2544.0lm	2584.0lm	2648.0lm
CRI	>90	>90	>90
Supply	48Vdc	48Vdc	48Vdc

Item	Temperature	Adapter	Disk	Stem
3408	M	-JBI		-BO
	W	-JNE		-BV
	N		-NO	
			-OR	
			-RR	
			-TI	

Per binario INCASSO for RECESSED track



	M 2700K	W 3000K	N 4000K
Power	13.6W	13.6W	13.6W
Nominal lumen	2544.0lm	2584.0lm	2648.0lm
CRI	>90	>90	>90
Supply	48Vdc	48Vdc	48Vdc

Item	Temperature	Adapter	Disk	Stem
3409	M	-JBI		-BO
	W	-JNE		-BV
	N		-NO	
			-OR	
			-RR	
			-TI	

Driver 48Vdc in tensione in remoto


Remote constant voltage drivers 48Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
1A0633	1-3	70W	IP20	210x45x49	ON-OFF
1A0634	1-9	150W	IP20	210x45x49	ON-OFF
1A1239	1-15	240W	IP67	244x68x39	ON-OFF
1A2493	1-20	320W	IP67	252x90x44	ON-OFF

Driver 48Vdc in tensione integrabili nel binario a plafone


Constant voltage drivers 48Vdc fully integrable into ceiling-mounted track

	Item	items powerable	Power	IP	Dimensions	Dimming
Colore Nero, Bianco su richiesta Black finish, White available on request	1A1681	1-5	100W	IP20	298x16x19	DALI

**Driver 48Vdc in tensione semi-integrabili nel binario a plafone**

Constant voltage drivers 48Vdc semi-recessed into ceiling-mounted track

	Item	items powerable	Power	IP	Dimensions	Dimming
Colore Nero, Bianco su richiesta Black finish, White available on request	1A2987	1-15	250W	IP20	268x43,5x22	DALI

**Centraline dimmerabili semi-integrabili nel binario**

Dimmable controllers semi-recessed into track

Permette di collegare 64 lampade DALI ripartite su 8 gruppi

Allows to connect up to 64 DALI lamps, splitted up to 8 groups

	Item	items powerable	Power	IP	Dimensions	Dimming
Colore Nero, Bianco su richiesta Black finish, White available on request	1A1426	1-64	8W	IP20	143x18x58	CASAMBI

