


INDOOR - SUSPENSION

POLY ESAGONO




- alluminio, policarbonato



- aluminum, polycarbonate

Con rosone e driver, cavi inclinati

With canopy and driver, slanted cables




9610	M 2700K	W 3000K
Power	↑17.3W ↓17.3W	↑17.3W ↓17.3W
Nominal lumen	↑1896.0lm ↓1896.0lm	↑2076.0lm ↓2076.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9610	M	-BV	-BR
	W	-OR	-OR

composed by
RS54 (1Pz)
9600 (1Pz)

Con rosone e driver, cavi inclinati

With canopy and driver, slanted cables




9611	M 2700K	W 3000K
Power	↑25.9W ↓25.9W	↑25.9W ↓25.9W
Nominal lumen	↑2844.0lm ↓2844.0lm	↑3114.0lm ↓3114.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9611	M	-BV	-BR
	W	-OR	-OR

composed by
RS54 (1Pz)
9601 (1Pz)

Con rosone e driver, cavi inclinati

With canopy and driver, slanted cables




9612	M 2700K	W 3000K
Power	↑34.6W ↓34.6W	↑34.6W ↓34.6W
Nominal lumen	↑3792.0lm ↓3792.0lm	↑4152.0lm ↓4152.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9612	M	-BV	-BR
	W	-OR	-OR

composed by
RS54 (1Pz)
9602 (1Pz)

Con rosone e driver, cavi inclinati

With canopy and driver, slanted cables




9617	M 2700K	W 3000K
Power	↑43.2W ↓43.2W	↑43.2W ↓43.2W
Nominal lumen	↑4740.0lm ↓4740.0lm	↑5190.0lm ↓5190.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9617	M	-BV	-BR
...composed by RS55 (1Pz) 9607 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi inclinati

With canopy and driver, slanted cables




9618	M 2700K	W 3000K
Power	↑64.8W ↓64.8W	↑64.8W ↓64.8W
Nominal lumen	↑7110.0lm ↓7110.0lm	↑7785.0lm ↓7785.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9618	M	-BV	-BR
...composed by RS55 (1Pz) 9608 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi inclinati

With canopy and driver, slanted cables




9613	M 2700K	W 3000K
Power	↑77.8W ↓77.8W	↑77.8W ↓77.8W
Nominal lumen	↑8532.0lm ↓8532.0lm	↑9342.0lm ↓9342.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9613	M	-BV	-BR
...composed by RS40 (1Pz) 9600 (1Pz) 9601 (1Pz) 9602 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi dritti

With canopy and driver, straight cables




9620	M 2700K	W 3000K
Power	↑17.3W ↓17.3W	↑17.3W ↓17.3W
Nominal lumen	↑1896.0lm ↓1896.0lm	↑2076.0lm ↓2076.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9620	M	-BV	-BR
...composed by RS52 (1Pz) 9600 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi dritti

With canopy and driver, straight cables




9621	M 2700K	W 3000K
Power	↑25.9W ↓25.9W	↑25.9W ↓25.9W
Nominal lumen	↑2844.0lm ↓2844.0lm	↑3114.0lm ↓3114.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9621	M	-BV	-BR
...composed by RS52 (1Pz) 9601 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi dritti

With canopy and driver, straight cables




9622	M 2700K	W 3000K
Power	↑34.6W ↓34.6W	↑34.6W ↓34.6W
Nominal lumen	↑3792.0lm ↓3792.0lm	↑4152.0lm ↓4152.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9622	M	-BV	-BR
...composed by RS52 (1Pz) 9602 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi dritti

With canopy and driver, straight cables




9627	M 2700K	W 3000K
Power	↑43.2W ↓43.2W	↑43.2W ↓43.2W
Nominal lumen	↑4740.0lm ↓4740.0lm	↑5190.0lm ↓5190.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9627	M	-BV	-BR
...composed by RS38 (1Pz) 9607 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi dritti

With canopy and driver, straight cables




9628	M 2700K	W 3000K
Power	↑64.8W ↓64.8W	↑64.8W ↓64.8W
Nominal lumen	↑7110.0lm ↓7110.0lm	↑7785.0lm ↓7785.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9628	M	-BV	-BR
.....composed by RS38 (1Pz) 9608 (1Pz)	W	-OR	-OR

Con rosone e driver, cavi dritti

With canopy and driver, straight cables



9623	M 2700K	W 3000K
Power	↑77.8W ↓77.8W	↑77.8W ↓77.8W
Nominal lumen	↑8532.0lm ↓8532.0lm	↑9342.0lm ↓9342.0lm
CRI	>94	>94
Supply	220-240V	220-240V

Item	Temperature	Canopy	Body
9623	M	-BV	-BR
.....composed by RS41 (1Pz) 9600 (1Pz) 9601 (1Pz) 9602 (1Pz)	W	-OR	-OR