



INDOOR - CEILING

SHINE SPOT

- alluminio

- aluminum



9351	M 2700K	W 3000K	N 4000K
Power	5.8W	5.8W	5.8W
Nominal lumen	515.0lm	555.0lm	555.0lm
CRI	>90	>90	>90
Supply	24Vdc	24Vdc	24Vdc
Item	Temperature	°Optic	Finish
9351	M	15	-BO
	W	36	-BV
	N		-NO
			-OR
			-TI

Driver 24Vdc in tensione in remoto

Remote constant voltage drivers 24Vdc

Item	items powerable	Power	IP	Dimensions	Dimming
1A0150	1-2	30W	IP20	154x50x14	ON-OFF
1A1910	1-4	60W	IP20	185x63,5x22	ON-OFF
1A1476	1-7	100W	IP20	177x56,4x17,2	ON-OFF
1A2168	1-7	100W	IP20	190x65x22	PUSH DALI
1A1999	1-7	100W	IP20	201x63x30	L-C

Centraline dimmerabili in remoto

Remote dimmable controllers

Item	Power	IP	Dimensions	Dimming
1A0837/24	144W	IP20	132x22x20	PUSH DALI 1-10V
1A0838/24	288W	IP20	164x38x25	PUSH DALI 0.1-10V