


INDOOR - CEILING RECESSED

TINY ADJUSTABLE GHOST




- alluminio, gesso

- aluminum, plaster



Ø145




| 4857 | M 2700K | W 3000K | N 4000K |
|----------------------|---------|---------|---------|
| Power | 6.6W | 6.6W | 6.6W |
| Nominal lumen | 700.0lm | 733.0lm | 785.0lm |
| CRI | >90 | >90 | >90 |
| Supply | 500mA | 500mA | 500mA |


| Item | Temperature | °Optic | Finish |
|-------------|-------------|-----------|------------|
| 4857 | M | 15 | -NA |
| | W | 38 | -BO |
| | N | 55 | -BV |
| | | | -OR |

Controcassa Outercasing

per 1 faretto
for 1 spotlight



per 2 faretti
for 2 spotlights



Item

CN19

CN21

Driver in corrente in remoto 500mA

500mA remote constant current driver


| Item | items powerable | Power | IP | Dimensions | Dimming |
|---------------|-----------------|-------|------|------------|---------|
| 1A2533 | 1 | 8W | IP20 | 132x22x19 | ON-OFF |

Convertitore da 24Vdc a 500mA

24Vdc to 500 mA converter

Necessita di driver remoto a 24Vdc

Requires 24V remote driver



| Item | items powerable |
|---------------|-----------------|
| 2A4843 | 1 |

Driver 24Vdc in tensione in remoto

Remote constant voltage drivers 24Vdc

| Item | items powerable | Power | IP | Dimensions | Dimming |
|---------------|-----------------|-------|------|---------------|-------------|
| 1A0150 | 1-2 | 30W | IP20 | 154x50x14 | ON-OFF |
| 1A1910 | 1-4 | 60W | IP20 | 185x63,5x22 | ON-OFF |
| 1A1476 | 1-7 | 100W | IP20 | 177x56,4x17,2 | ON-OFF |
| 1A2168 | 1-7 | 100W | IP20 | 190x65x22 | PUSH DALI |
| 1A1999 | 1-7 | 100W | IP20 | 201x63x30 | L-C |

Centraline dimmerabili in remoto

Remote dimmable controllers

| Item | Power | IP | Dimensions | Dimming |
|------------------|-------|------|------------|-----------------------|
| 1A0837/24 | 144W | IP20 | 132x22x20 | PUSH DALI 1-10V |
| 1A0838/24 | 288W | IP20 | 164x38x25 | PUSH DALI 0.1-10V |