

OUTDOOR


TERRA INCASSO / FLOOR BUILT-IN

MINI DOT UP LIGHT



- alluminio, acciaio inox 316,
vetro


- aluminum, stainless steel
316, glass



Corpo con ghiera Ø52 / Body with ring Ø52

	M 2700K	W 3000K	N 4000K
133			
Potenza/ Power	1x5.8W	1x5.8W	1x5.8W
Nominal lumen	1x515lm	1x555lm	1x555lm
CRI	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc


Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
133	M	00	-AI
	W	15	
	N	36	




Corpo con ghiera Ø70 / Body with ring Ø70

	M 2700K	W 3000K	N 4000K
135			
Potenza/ Power	1x5.8W	1x5.8W	1x5.8W
Nominal lumen	1x515lm	1x555lm	1x555lm
CRI	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc

Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
135	M	00	-AI
	W	15	
	N	36	



Controcassa / Outercasing



Articolo
Item

CN08

Driver 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc

Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0143	1	14W	IP67	85x39x19	ON-OFF
1A0148	1-2	30W	IP67	131x42x34	ON-OFF
1A0149	1-6	75W	IP67	155x50x32	ON-OFF
1A2386	1-16	120W	IP67	191x63x37,5	DALI
1A2387	200W	IP67	195x68x39,5	DALI PUSH	