

INDOOR

SOFFITTO / CEILING

EYE SPOT




- alluminio

- aluminum



	M 2700K	W 3000K	N 4000K
Potenza/ Power	1x6.6W	1x6.6W	1x6.6W
Nominal lumen	1x700lm	1x733lm	1x785lm
CRI	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc



Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
3780	M	14	-BO
	W	36	-BV
	N		-NO
			-OR
			-TI

Driver 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc

Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0530	1	8W	IP20	42x40x22	ON-OFF
1A0150	1-2	30W	IP20	154x50x14	ON-OFF
1A1910	1-4	60W	IP20	185x63,5x22	ON-OFF
1A1476	1-7	100W	IP20	177x56,4x17,2	ON-OFF
1A2168	1-7	100W	IP20	190x65x22	PUSH DALI
1A1999	1-7	100W	IP20	201x63x30	L-C

Centraline dimmerabili in remoto / Remote dimmable controllers

Articolo Item	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming	
1A0837/24	144W	IP20	132x22x20	PUSH DALI 1-10V	
1A0838/24	288W	IP20	164x38x25	PUSH DALI 0-10V 1-10V	
Controller 1 canale - DC 1-channel controller - DC	1A0172/24	288W	IP20	57x44x25	PUSH CASAMBI