


SOFFITTO INCASSO / CEILING BUILT-IN

MAXI DOT DOWN LIGHT Ø100




Alluminio, inox 316 e vetro
Fascio di luce verso il basso
Driver: escluso


Aluminum, stainless steel 316 and glass
 Light beam: downward-projected
 Driver: excluded



| 116 | M 2700°K | W 3000°K | N 4000°K | RGBW RGB+3000°K |
|------------------------------|-----------------|-----------------|-----------------|------------------------|
| Potenza/ Power | 1x 9,1W | 1x 9,1W | 1x 9,1W | 1x 7,9W |
| Lumen | 1x 1119 lm | 1x 1166 lm | 1x 1189 lm | 1x 465lm |
| CRI | >90 | >90 | >90 | >90 |
| Alimentazione/ Supply | 24Vdc | 24Vdc | 24Vdc | 24Vdc |



| Articolo Item | Temperatura Temperature | °Optica °Optic | Finitura Finish |
|---------------|-------------------------|----------------|-----------------|
| 116 | M | 00 | -Al |
| | W | 12 | |
| | N | 35 | |
| | | 55 | |



| | | | |
|------------|-------------|-----------|------------|
| 116 | RGBW | 24 | -Al |
| | | 36 | |
| | | 60 | |

La versione RGBW necessita della Centralina RGBW + Alimentatore in 24Vdc in tensione

RGBW version requires constant voltage driver 24Vdc + driver RGBW

Alimentatori 24Vdc in tensione / Constant voltage drivers 24Vdc

| Articolo Item | Potenza Power | IP | Dimensioni Dimensions | N° art. alimentabili N° of items powerable |
|---------------|---------------|------|-----------------------|--|
| 1A0143 | 14W | IP67 | 90x39x19 | 1 |
| 1A0148 | 30W | IP67 | 175x42x34 | 1-2 |
| 1A0149 | 75W | IP67 | 200x50x32 | 1-4 |
| 1A0147 | 240W | IP67 | 244x68x39 | 1-18 |

Controller per versione RGBW / Controller for RGBW version

| Articolo Item | Potenza Power | IP | Dimensioni Dimensions | N° art. alimentabili N° of items powerable |
|------------------|------------------|------|--------------------------|---|
| 2A4314 | 67W MAX | IP67 | 90x71x58 | 1-7 |
| 2A4315 | 67W MAX | IP67 | 90x71x58 | 1-7 |