







SOFFITTO / CEILING


**SHINE SPOT**

**Ottone**  
**Fascio di luce orientabile**  
**Driver: escluso**

Brass  
 Light beam: adjustable  
 Driver: excluded

<b>9351</b>	<b>M 2700K</b>	<b>W 3000K</b>	<b>N 4000K</b>
<b>Potenza/ Power</b>	1x 5,8W	1x 5,8W	1x 5,8W
<b>Lumen</b>	1x 445 lm	1x 480 lm	1x 515 lm
<b>CRI</b>	>90	>90	>90
<b>Alimentazione/ Supply</b>	24Vdc	24Vdc	24Vdc

Articolo Item	Temperatura Temperature	°Optica °Optic	Finitura Finish
<b>9351</b>	<b>M</b>	<b>15</b>	<b>-BO</b> 
	<b>W</b>	<b>36</b>	<b>-BV</b> 
	<b>N</b>		<b>-NO</b> 
			<b>-OR</b> 
			<b>-OS</b> 
			<b>-TI</b> 

**Alimentatori 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc**

Articolo Item	Potenza Power	IP	Dimensioni Dimensions	N° art. alimentabili N° of items powerable	Dimmer
<b>1A0150</b>	30W MAX	IP20	160x58x18	1-2	-
<b>1A0151</b>	50W MAX	IP20	160x58x18	1-4	-
<b>1A0152</b>	75W MAX	IP20	160x58x18	1-6	-
<b>1A0145</b>	100W MAX	IP67	190x52x33	1-9	-
<b>1A0153</b>	150W MAX	IP20	240x60x49	1-13	-

**Centraline dimmerabili in remoto / Remote dimmable controllers**

Articolo Item	Potenza Power	IP	Dimensioni Dimensions	Dimmer
<b>1A0837</b>	144W MAX	IP20	132x22x19	1-10V   DALI   PUSH
<b>1A0838</b>	288W MAX	IP20	150x38x25	0-10V   1-10V   DALI   PUSH
<b>1A0172</b>	240W MAX	IP20	57x43x19	CASAMBI   PUSH

Controller 1 canale - DC

Controller 1 channel - DC